

## Friendly Index Sets of $n$ -galaxies

Sin-Min Lee, Richard M. Low\*, H.K. Ng and Yung-Chin Wang; San Jose State University

Let  $G$  be a graph with vertex set  $V(G)$  and edge set  $E(G)$ . A vertex labeling  $f : V(G) \rightarrow \mathbb{Z}_2$  induces an edge labeling  $f^* : E(G) \rightarrow \mathbb{Z}_2$  defined by  $f^*(xy) = f(x) + f(y)$ , for each edge  $xy \in E(G)$ . For  $i \in \mathbb{Z}_2$ , let  $v_f(i) = |\{v \in V(G) : f(v) = i\}|$  and  $e_f(i) = |\{e \in E(G) : f^*(e) = i\}|$ . We say that  $f$  is *friendly* if  $|v_f(1) - v_f(0)| \leq 1$ . The *friendly index set* of  $G$ , denoted by  $\text{FI}(G)$ , is defined as  $\text{FI}(G) = \{|e_f(1) - e_f(0)| : \text{vertex labeling } f \text{ is friendly}\}$ . An  *$n$ -galaxy* is a disjoint union of  $n$  stars. In this paper, we establish the friendly index sets for various classes of  $n$ -galaxies.

Key words: friendly labeling, friendly index set, graph labeling.